

TELESIS

DTS 7 HD



Designer and Manufacturer Company:

Telesis Telekomünikasyon Sistemleri San. Ve Tic. A.Ş.

Asağı Ovecler mah.

1314cad. 1306 sok

Çankaya

Tel: +90 312 384 0540

Fax: +90 312 384 0549

<http://www.telesis.com.tr>



Warnings and Precautions (Safety Instructions)



This system should be installed and serviced only by qualified personnel who has the necessary training about electrical equipment, and who understands the hazards that can arise when working on this type of equipment.



Your set may be damaged if the Ethernet cable is unplugged and plugged in while your set is on..



Your set may contain devices that generate electricity, smoke, dust, gas or radiation, such as generators, copiers, radios, etc. It should not be in the same environment with high frequency generating devices.



Do not place items on your set..



Do not expose your set to direct sunlight.



Keep your set in a humidity-free environment.



!

Rules to be followed in Maintenance, Repair and Use

- Do not remove and install cables and screws while your set is in operation..
- After the maintenance/installation of your set is completed, check that all connections are correct before leaving the place where it is installed..
- Make sure all connectors are securely connected..
- Make sure that the items described in the product setup section are followed.

Matters to be Considered During Handling and Shipping

- The product should be transported in such a way that it will not break.
- The product should be transported away from moisture and water.

Hazardous to Human and Environmental Health during Use or Warnings Regarding Potentially Harmful Situations

- Setinizin kurulumunu ve bakımını Telesis Yetkili Satış ve Servis noktalarına yaptırınız. Setinizi çalıştırmadan önce montaj ve kullanım talimatları mutlaka okunmalıdır.
- Setin bulunduğu ortam nem ve sudan uzak olmalıdır.

	DTS 7 HD
Screen size	7"
Screen resolution	800 x 480
Display Type	TFT LCD
Touch screen	Yes
Screen angle	27° - 90°
Power	Line Feed 48v DC
Width x Length x Depth (*)	19 x 24.1 x 3.6
Total weight	1050gr
Weight handset	150gr
External microphone	3.5mm Jack
External headphone	3.5mm Jack
Line connection	RJ11 1pair
Handset connection	RJ4 2 pair
Handset spiral	Twisted Pair
HF Mik. connection	Twisted Pair
Expansion slot	Yes
Handsfree Mode	Full Duplex
Voice records	One key
Silent	One key
Speed dial keys	Via Touch Screen
Non-slip feed	Rubber 4
Software update	Uninterrupted from the exchange
Handset volume	Adjustable 8 Levels
HF volume	Adjustable 8 Levels

Ring volume	Adjustable 8 steps
Ring melody	Polyphonic
Keypad	64 x Rubber
Plastic Thickness	3mm

Recommended Working Conditions

- Temperature: 0-45 °C
- Humidity: 0-85% (non-condensing)