

TELESIS

X Series

(DTS X - ITS X - BDP X)



Designer and Manufacturer Company:

Telesis Telekomünikasyon Sistemleri San. Ve Tic. A.Ş.

Asağı Oveçler mah. 1314 cad. 1306 sok Çankaya

Tel: +90 312 384 0540

Faks: +90 312 384 0549

<http://www.telesis.com.tr>



Warnings and Precautions (Safety Instructions)



This system should be installed and serviced only by qualified personnel who has the necessary training about electrical equipment, and who understands the hazards that can arise when working on this type of equipment.



Your set may be damaged if the Ethernet cable is unplugged and plugged in while your set is on..



Your set may contain devices that generate electricity, smoke, dust, gas or radiation, such as generators, copiers, radios, etc. It should not be in the same environment with high frequency generating devices.



Do not place items on your set..



Do not expose your set to direct sunlight.



Keep your set in a humidity-free environment.



Rules to be followed in Maintenance, Repair and Use

- Do not remove and install cables and screws while your set is in operation..
- After the maintenance/installation of your set is completed, check that all connections are correct before leaving the place where it is installed..
- Make sure all connectors are securely connected..
- Make sure that the items described in the product setup section are followed.

Matters to be Considered During Handling and Shipping

- The product should be transported in such a way that it will not break.
- The product should be transported away from moisture and water.

Hazardous to Human and Environmental Health during Use or Warnings Regarding Potentially Harmful Situations

- Have your set installed and maintained by Telesis Authorized Sales and Service points. Before operating your set, the assembly and operating instructions must be read.
- The environment should be away from moisture and water..

Information on Usage Errors

- It should not be in the same environment with high frequency generating devices..
- The set should not be exposed to direct sunlight.

Identifier Properties

	DTS X
Screen size	4.3"
Screen resolution	480 x 272
Display Type	TFT LCD
Screen Angle	Gradual
Güç Ünitesi	Line Feed 48v DC
Width x Length x Depth (*)	18.3 x 19.2 x 4.4
Weight Total	605gr
Weight Handset	145gr
External Microphone	RJ4 2 pair
External Headphone	RJ4 2 pair
Line Connection	RJ11 1 pair
Handset connection	RJ4 2 pair
Handset Spiral	Twisted Pair
HF Mic.	Onboard
Expansion slot	Yes
Handsfree Mode	Full Duplex
Voice recors	One key
Silent	One key
Function, speed dial keys	8 bases with LED Display and LCD Display Interactive
Non-Slip Feet	6 x EPDM
Software update	Uninterrupted from the exchange
Handset Volume	Adjustable 8 Levels
HF volume	Adjustable 8 Levels
Ring volume	Adjustable 8 Levels
Ring Melody	Polyphonic
Keypad	43 pcs of High Strength Rubber

Plastic Thickness	3mm
--------------------------	-----

Package Included

- Digital Telephone Set (DTS X)
- IP xSip Telephone Set (ITS X)
- Busy display panel (BDP X)
- Handset (DTS X, ITS X)
- Handset spiral (DTS X, ITS X)
- User manual
- RJ45 Ethernet cable (ITS X)

Recommended Working Conditions

- Temperature: 0-45 °C
- Humidity: 0-85% (non-condensing)